

FLOORING STANDARDS

Timeless Comfort

SHERATON

FLOORING STANDARDS

Timeless Comfort



Guestroom | 296747

Style	42KRY
Color	Z854F
Product Type	Broadloom
Fiber	Eco Solution Q® Nylon
Dye Method	100% Solution Dyed
Construction	Multi-Level Pattern Cut/Loop
Tufted Weight	32.0 oz/yd ² 1085.01 g/m ²
Gauge	1/10 in 39.4 per 10 cm
Stitches	10.83 per in 42.6 per 10 cm
Size	13 ft 6 in 4.11 m
Pattern Repeat	72 in x 78 in 1.83 m x 1.98 m
Backing	Classicbac®
Installation	Stretch-In
Warranty	10 Year Commercial Limited



For sample, order BS075 color Z854F.

FLOORING STANDARDS

Timeless Comfort



For sample, order BS081 color Z790K.

Guestroom | 296900

Style	42KRX
Color	Z790K
Product Type	Broadloom
Fiber	Eco Solution Q® Nylon
Dye Method	100% Solution Dyed
Construction	Multi-Level Pattern Cut/Loop
Tufted Weight	32.0 oz/yd ² 1085.01 g/m ²
Gauge	1/10 in 39.4 per 10 cm
Stitches	10.83 per in 42.6 per 10 cm
Size	13 ft 6 in 4.11 m
Pattern Repeat	72 in x 78 in 1.83 m x 1.98 m
Backing	Classicbac®
Installation	Stretch-In
Warranty	10 Year Commercial Limited

Timeless Comfort



Guestroom Carpet Tile Rug Inset | 303489

Style	42KV3
Color	Z345Q
Product Type	Carpet Tile
Fiber	Eco Solution Q® Nylon
Dye Method	100% Solution Dyed
Construction	Multi-Level Pattern Cut/Loop
Tufted Weight	30.0 oz/yd ² 1017.2 g/m ²
Gauge	1/10 in 39.4 per 10 cm
Stitches	10.17 per in 40.04 per 10 cm
Size	9 in x 36 in 22.86 cm x 91.44 cm
Backing	Ecworx® Tile
Installation	Direct Glue or Double Stick
Approved Install Method	Ashlar
Warranty	Lifetime Commercial Limited



For sample, order BS076 color Z345Q.

Timeless Comfort



For sample, order BS077 color Z346Q.

Guestroom Carpet Tile Rug Inset | 303488

Style	42KV3
Color	Z346Q
Product Type	Carpet Tile
Fiber	Eco Solution Q® Nylon
Dye Method	100% Solution Dyed
Construction	Multi-Level Pattern Cut/Loop
Tufted Weight	30.0 oz/yd ² 1017.2 g/m ²
Gauge	1/10 in 39.4 per 10 cm
Stitches	10.17 per in 40.04 per 10 cm
Size	9 in x 36 in 22.86 cm x 91.44 cm
Backing	Ecoworx® Tile
Installation	Direct Glue or Double Stick
Approved Install Method	Ashlar
Warranty	Lifetime Commercial Limited

Timeless Comfort



Guestroom | 284391

Style	BS103
Color	00100
Construction	Luxury Vinyl Tile with Attached Acoustic Backing
Wear Layer Thickness	20 mil 0.02 in 0.51 mm
Overall Thickness	0.197 in 5.0 mm
Nominal Dimensions	7 in x 48 in 18 cm x 122 cm
Actual Dimensions	7 in x 48 in 17.78 cm x 121.92 cm
Installation	Direct Glue
Approved Install Method	Stagger
Area Per Box	23.33 sq ft 10 pcs per box
Warranty	15 Year Commercial Limited



For sample, order BS103 color 00100.

Timeless Comfort



For sample, order BS068 color Z469J.

Corridor Runner | 299659

Style	42KR4
Color	Z469J
Product Type	Broadloom
Fiber	Eco Solution Q® Nylon
Dye Method	100% Solution Dyed
Construction	Multi-Level Loop Tip Shear
Tufted Weight	36.0 oz/yd ² 1220.64 g/m ²
Gauge	1/10 in 39.4 per 10 cm
Stitches	10 per in 39.37 per 10 cm
Size	12 ft 3.66 m
Pattern Repeat	72 in x 147.2 in 1.83 m x 3.70 m
Backing	Ultraloc®
Installation	Direct Glue or Double Stick
Warranty	Lifetime Commercial Limited



For sample, order BS069 color Z575L.

Corridor Outfill | 299642

Style	42KR4
Color	Z575L
Product Type	Broadloom
Fiber	Eco Solution Q® Nylon
Dye Method	100% Solution Dyed
Construction	Multi-Level Loop Tip Shear
Tufted Weight	36.0 oz/yd ² 1220.64 g/m ²
Gauge	1/10 in 39.4 per 10 cm
Stitches	10 per in 39.37 per 10 cm
Size	12 ft 3.66 m
Pattern Repeat	36 in x 36 in 0.91 m x 0.91 m
Backing	Ultraloc®
Installation	Direct Glue or Double Stick
Warranty	Lifetime Commercial Limited

FLOORING STANDARDS

Timeless Comfort



Corridor I C-11

-  Elevator Lobby
-  Doorfill
-  Corridor

Timeless Comfort

Additional Product Options

Public Space Cushion

Style	DW206
Description	DuraWorx
Weight	47 oz 1,593 g/m ²
Thickness	0.20 in 5.08 mm
Density	19 lb/ft ³ 304 kg/m ³
Square Yards Per Roll	30

Broadloom Adhesive

Style	H1000
Description	Shaw 1000 4 gallon pail
Spread Rate	8-10 sy per gallon

Carpet Tile Adhesive

Style	H5000
Description	Shaw 5000 4 gallon pail
Spread Rate	28-33 sy per gallon

Seam Sealer

Style	H4000
Description	Shaw 4000 1 quart
Spread Rate	550-600 lf per quart

LVT Adhesive

Style	O12VS
Description	Shaw 4100 4 gallon pail
Spread Rate	175-225 sf per gallon

